



ORxxxF52384OR1-W3

Electronic features



Technical parameters


LED Type	0620
LED/m	384
Voltage range	12V
Max power (24.0V)	7 W/m
Led color binning	5step MacAdam
Useful life span	20000h
Operating current (single LED)	12mA
Copper thickness	70 µm
Operating temperature	-10°C ~ +45°C
Max led temperature	65°C
IP rate	IP20
Emitting angle	140°



Lighting parameters

CCT	CRI	Rf	Rg	Lm/m	Lm/W	Energy rating
3000K (300)	CRI Ra>90	90	98	800	127	E
4000K (400)	CRI Ra>90	90	98	800	127	E

Dimensions



Specifications

PCB width	3 mm
Led strip height	2 mm
Cutting unit 12V	20,8 mm (8 led)
LED Pitch	2 mm
Reel length	5 m
Adhesive tape	3M 9495LE
Cable cross-section	0,75 mm²

ORxxxF52384OR1-W3

Product Range

Version	Temperature	IP type	Strip length	PCB colour	Led/m	LED type	Manufacturer No.	Input voltage	Misc.
OR	300	F	5	2	384	O	R	1	-W3
OR	400	F	5	2	384	O	R	1	-W3

Packaging

Technical parameters	
Carton dimension	520 x 170 x 330 mm
Quantity per carton	50
Net weight	65 g
Gross weight	73 g



250 m per carton



5 meters per carton roll



1 roll per carton box

Orizzonte uses paper boxes and reels for its LED strips to fight for a plastic free world.

Certifications

