

ORxxx-F52-384OR2-W10

Electronic features



COB



CRI Ra>90



IP20



24V



Orizzonte
LED Lighting

www.orizzonteled.com

info@orizzonteled.com

Technical parameters


LED Type	0620
LED/m	384
Voltage range	24V
Max power (24.0V)	10 W/m
Led color binning	5step MacAdam
Useful life span	20000h
Operating current (single LED)	17mA
Copper thickness	70 µm
Operating temperature	-10°C ~ +45°C
Max led temperature	65°C
IP rate	IP20
Emitting angle	120°



Lighting parameters

CCT	CRI	Rf	Rg	Lm/m	Lm/W	Energy rating
3000K (300)	CRI Ra>90	89	96	760	84	G

Dimensions



Specifications

PCB width	10 mm
Led strip height	2 mm
Cutting unit 24V	31,2 mm (16 led)
LED Pitch	4 mm
Reel length	5 m
Adhesive tape	<u>3M 9495LE</u>
Cable cross-section	0,75 mm ²

ORxxx-F52-384OR2-W10

Product Range

Version	Temperature	IP type	Strip length	PCB colour	Led/m	LED type	Manufacturer No.	Input voltage	Misc.
OR	300	F	5	2	384	O	R	2	-W10

Packaging

Technical parameters	
Carton dimension	325 x 290 x 145 mm
Quantity per carton	50
Net weight	127 g
Gross weight	137 g



250 m per carton



5 meters per carton roll



1 roll per carton box

Orizzonte uses paper boxes and reels for its LED strips to fight for a plastic free world.

Certifications

