

OR-xxx-F52400OR2-W5-S1

Electronic features



www.orizzonteled.com
info@orizzonteled.com

Technical parameters

LED Type	0620
LED/m	400
Voltage range	24V
Max power (24.0V)	11 W/m
Led color binning	5step MacAdam
Useful life span	20000h
Operating current (single LED)	9mA
Copper thickness	108 µm
Operating temperature	-10°C ~ +45°C
Max led temperature	65°C
IP rate	IP20
Emitting angle	140°



Lighting parameters

CCT	CRI	Rf	Rg	Lm/m	Lm/W	Energy rating
4000K (400)	CRI Ra>90	96	104	980	99	F

Dimensions

Specifications

PCB width	5 mm
Led strip height	2 mm
Cutting unit 24V	20 mm (8 led)
Reel length	5 m
Adhesive tape	3M 9495LE
Cable cross-section	0,75 mm ²

OR-xxx-F52400OR2-W5-S1

Product Range

Version	Temperature	IP type	Strip length	PCB colour	Led/m	LED type	Manufacture r No.	Input voltage	Misc.
OR	400	F	5	2	400	O	R	2	-W5-S1

Packaging

Technical parameters

Carton dimension	430 x 310 x 170 mm
Quantity per carton	50
Net weight	95 g
Gross weight	144 g



5 meters per carton roll



1 roll per carton box

250 m per carton

Orizzonte uses paper boxes and reels for its LED strips to fight for a plastic free world.

Certifications

