


ORxxx-F52-480OR2A

Electronic features



www.orizzonteled.com
info@orizzonteled.com

Technical parameters


LED Type	0620
LED/m	480
Voltage range	24V
Max power (24.0V)	7,5 W/m
Led color binning	5step MacAdam
Useful life span	20000h
Operating current (single LED)	16mA
Copper thickness	70 µm
Operating temperature	-10°C ~ +45°C
Max led temperature	65°C
IP rate	IP20
Emitting angle	140°



Lighting parameters

CCT	CRI	Rf	Rg	Lm/m	Lm/W	Energy rating
4000K (400)	CRI Ra>90	96	104	665	99	F

Dimensions



Specifications

PCB width	8 mm
Led strip height	2 mm
Cutting unit 24V	50 mm (24 led)
LED Pitch	4,9 mm
Reel length	5 m
Adhesive tape	<u>3M 9495LE</u>
Cable cross-section	0,75 mm ²

ORxxx-F52-480OR2A

Product Range

Version	Temperature	IP type	Strip length	PCB colour	Led/m	LED type	Manufacturer No.	Input voltage	Misc.
OR	400	F	5	2	480	O	R	2	A

Packaging

Technical parameters	
Carton dimension	325 x 290 x 145 mm
Quantity per carton	50
Net weight	103 g
Gross weight	113 g



250 m per carton



5 meters per carton roll



1 roll per carton box

Orizzonte uses paper boxes and reels for its LED strips to fight for a plastic free world.

Certifications

